

GB-38R / 36R / 34R 1,000 PTO POWERED ORCHARD SPRAYER



550R / 22.5 Alliance Tread Tire
Standard Feature



Standard



Option



Option



Standard Feature

Hydraulic Spray Valves

2-Point Turning Hitch

DK Turning Hitch

Adjustable Air Vanes

Davis & Davis Distributors
507 E. Dinuba Avenue • Reedley, Ca 93654
(Ph)559-638-6546 • (Fax)559-638-9262
Visit us: www.airofan.com • Contact us: info@airofan.com



GB-38R, 36R, 34R 1,000 GALLON PTO DRIVE SPRAYER

Myers 2-Stage Centrifugal Pump

STANDARD FEATURES

- 1000 Gallon 304 stainless steel tank
- 44 GPM / 600 PSI Comet® diaphragm pump
- 38", 36", & 34" reverse 8-blade axial flow steel fans
- 2 speed gearbox with neutral
- DK turning hitch w/std. U-Joint PTO shaft
- HD size 6 tank driveline
- 1" 304 stainless steel mechanical agitation
- Dual or single hydraulic spray control vavles
- 304 stainless steel strainers
- Teejet® TXR Conejet ceramic nozzles
- 550R / 22.5 Alliance tread tire package
- Galvanized Reverse fan housing technology
- Heavy duty adjustable hubs and spindles
- Composite nylon adjustable air vanes w/ specialty valves



OPTIONS

- Air-O-Fan 90° DK turning hitch and 2-Point turning hitch
- Double or single lip swivel hitch (straight tongue only)
- 100 GPM / 140 PSI Myers® 2-stage centrifugal pump
- 53 GPM / 600 PSI Comet® Pump (Model IDS 2200)
- Morse cable and KZ Co. electric spray valves
- 2" and 3" Stainless steel fill connections
- Rear leaf guard
- Indented tank w/11.25x24" ribbed implement tires.
- Tree sensing & flow monitoring systems



SPECIFICATIONS

Length.....17' 10"
Width.....103"
Height.....71" to 79"
Weight.....4,650 lbs. (empty)
Air velocity.....130 mph (approx.)



Visit our website: www.airofan.com